

Non-maintained / Maintained

Emergency Bulkhead Lighting Enclosure

K10001 / K10002



Key Features

Attractive and tough slim line design.


- To ease installation the fittings have a hinged gear tray.
- The IP65 rated units are provided with grey base, prismatic diffuser and include 8W TS lamp.
- Non-maintained & maintained options.
- Screw down diffuser IP6S.
- Base and diffuser unmanufactured in tough, vandal resistant polycarbonate.
- 5 x 20mm knock outs for additional functions.
- 8W TS fluorescent lamp included.
- Designed BS EN 60598-2-22 IL Emergency lumens = 110 lumens
- Ballast lumen factor = 0.24

Model	K10001	K10002
Mode	Non-maintained	Maintained
Duration	3 hours	
Input voltage	230-240V - 50Hz	
Circuit Watts	8W	
Battery Type	High temp Ni-Cd battery	
Recharge Time	24 hours	
Temp Range	-10°C to +40°C	

Overview

The emergency bulkhead is designed to be both compact and tough, making it suitable for a variety of applications, both external and internal.

- Public buildings & car parks
- Industrial facilities & factories
- General lighting of stairwells
- Canopies or corridors



Lamp: 8W T16 Maintained

DLOR: 0.7

LMC (Luminaire Maint. Category): E

LOR: 0.84

Escape route		Max spacing (m)	
Min illum (lux)	Mounting height (m)	Centre to end	Between centres
1.0 trans	2.5	1.55	5.20
	3	1.05	5.00
1.0 axial	2.5	1.4	4.30
	3	1.05	4.20

Open area		Max spacing (m)			
Min illum (lux)	Mounting height (m)	Centre to end		Between centres	
		Trans	Axial	Trans	Axial
0.5	2.5	1.85	1.85	6.60	6.2
	3	1.8	1.8	6.90	6.5
	3.5	1.65	1.65	7.10	6.70



Illumino Ignis Ltd

LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

t.0203 00 44 855 f.0203 00 44 866 email sales@illuminoignis.co.uk

Unit 8, Tower Square, Tower Close, Huntingdon, PE29 7DT

www.illuminoignis.co.uk